

HYUNDAI

POWER EQUIPMENT

Diesel Generator
Standby Power 125KVA
3 Phase 1500 rpm

DHY125KSE



All Days | Safty | Reliable | Stability



TECHNICAL SPECIFICATION

DHY125KSE CANOPY TYPE

50Hz

Standby 125KVA

Benefits and Feature

- > Use best quality vehicle engine, low fuel consumption, running reliable
- > Use high quality and performance brushless alternator, with AVR
- > High quality controller of DEESEA
- > Block design electrical control system, easy operate and maintenance
- > Standard 8 hours generator running base frame fuel tank (100% load)
- > With baseframe forklift hole and generator canopy lifting hole
- > Industrial waterproof canopy, ensure generator all days running
- > Industrial silencer (7 meters the noise is lower than 72 dB)
- > Easy operation , IP23 protection industrial sockets and plugs
- > Four pole circuit breaker with RCD earth protection
- > Standard ATS function connector

Technical Specification

Prime Power	KVA/ KW	113/90
Standby Power	KVA/ KW	125/100
Power Factor		0.8
Frequency	Hz	50
Rate Voltage	V	400/ 230
Rate Current	A	171.7
Controller	DEESEA DSE6120	
Control Voltage	DC / V	24
Phase	3 phases, 4 wires	
Coolant Capacity (Engine only)	L	6.8
Fuel Tank Capacity (Base frame)	L	198
Fuel Consumption (100% load)	L/hour	28.3
Running Time	Hour	7

Voltage

Steady state regulation	%	$\leq \pm 1$
Dynamic voltage renewal	%	$\leq +20 \sim -15$
Stable time	Sec	20
Waveform distortion	%	≤ 3
Volatility		≤ 0.5

Frequency

Steady state regulation	%	$\leq \pm 1$
Dynamic frequency renewal	%	$\leq +10 \sim -7$
Stable time	Sec	20
Volatility		≤ 0.5

Environment require

Temperature	C	≤ 50
Humidity	%	≤ 90
Altitude	m	≤ 1000

Standard

ISO3046, ISO8528, ISO9001-2008

Dimension | Weight | Sound



DHY125KSE CANOPY TYPE

Length (L)	mm	2688
Weight (W)	mm	1080
Height (H)	mm	1450
Weight net	kg	1725
loading capacity (units/container)		
Sound @7 meter	db	72

Note

1. Generator continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hours period
2. Every generator strictly test on 0%, 25%, 75%, 100%, 110% load dynamic responsiveness ability, and all protections

SDEC DIESEL ENGINE



Powerful engine and reliable running quality

Durable running performance and was proofed by vehicle's application

Compact structure

Compact structure and metal materials saving for low cost

Low maintenance and repair cost

Air, fuel and oil tubes are silicone and stainless steel materials, which reduce leakage problems substantially

Excellent start performance

Fuel injector and pump were tested fully in various environments, which provide excellent start and running performance

Model	4HTAA4.3-G23	
Prime power	Kw	105
Structure	4 cylinder	
Fuel type	Diesel	
Fuel consumption	L/Hour	28.3
Lubricant consumption	L/Hour	0.08
Governor	Electronic	
Cooling	Water-cooled	
Lubricant capacity	L	13
Air intake flow	m ³ /min	8.0
Exhaust gas flow	m ³ /min	19.1
Exhaust gas temperature	°C	600
Exhaust gas back pressure	KPa	8
Compression ratio	16:1	
Aspiration	Turbocharged	
Bore	mm	105
Stroke	mm	124
Displacement	L	4.3
SAE		
Dimension	mm	1080*738*1078
Weight	Kg	450

BALANTY ALTERNATOR

A brand of HYUNDAI CORPORATION

Model	AL274D	
Prime power	kVA	120
Structure	1 bearing	
Excitation mode	Self-excitation	
Insulation class	H	
Protection class	IP23	
TIF	<50	
THF	<2%	
Air flow	m ³ /s	0.216
Voltage regulation	AVR	



Best structure

Excellent design ensures compact structure and perfect appearance

Excellent performance

Excitation enhanced system improves start and short circuit's protection performance

Economy

Less parts involved and the most market's demand lead to cheap price and fine quality

Easy maintenance and repair

Core parts won't be involved in repair job, AVR can be replaced easily, examining diode doesn't disassemble rotor.

CONTROL PANEL



Measurement, displayment

Genset prime power Kw	●
Power factor	●
Engine speed	●
Phase to neutral voltage	●
Phase to phase voltage	●
Genset frequency	●
Genset current	●
Mains Phase to neutral voltage	○
Mains Phase to phase voltage	○
Mains frequency	○
Engine oil pressure	●
Engine water temperature	●
Fuel level	●
Battery voltage	●
Genset power KVA	●
Genset running time	●
Genset output KWh	●
History file	●

Alarm, shutdown function

Low oil pressure warning,shutdown	●
High water temperature warning,shutdown	●
Engine over and under speed shutdown	●
Low fuel level warning , shutdown	●
Battery low and high voltage warning	●
Battery charging failure	●
Genset low and high voltage warning, shut down	●
Alternator 3 phase voltage unbalance shut down	●
Alternator low and high frequency warning,shut down	●
Genset over load shutdown	●
Alternator 3 phase current unbalance shutdown	●
Mains low and high voltage warning	○
Mains low and high frequency warning	○

Optional

Remote start and stop	●
RS232 card	x
USB card	●
RS485 card	○
Multi language display	○
GPRS communication	○
GPS communication	○


● standard ○ optional x None

Deepsea DSE6120



DSE6110/20 MKIII
AUTO START & AUTO MAINS (UTILITY)
FAILURE CONTROL MODULES

ACCESSORIES



Exhaust system



Residential muffler

Exhaust gas pipe

Preheating system



Water preheater

Oil preheater

alternator Anti-condensation heater

Fuel system



Auto filling fuel pump

Manual filling fuel pump

500L base frame fuel tank

1000L base frame fuel tank

500L External fuel tank

1000L External fuel tank

Electrical system



Deepsea controller

IC-NT
synchronizing
controller

wireless remote starter

Maintenance spare parts



500 hours genset spare parts

1000 hours genset spare parts